


A
T ≥ 3mm, Form VA



Caps DIN 28013 - EN 10 028-2 - P265GH					
DN	D		T	H	kg/pc
	mm	inch			
20	26,9	¾	3,0	17,0	0,06
	30,0		3,0	18,0	0,06
	31,8		3,0	18,5	0,07
25	33,7	1	3,0	19,0	0,07
	38,0	1 ¼	3,0	20,0	0,08
	42,4	1 ¼	3,0	21,0	0,10
32	44,5	1 ½	3,0	21,5	0,11
	48,3	1 ½	3,0	22,5	0,11
	51,0		3,0	23,5	0,16
40	57,0	2	4,0	28,0	0,26
	60,3	2	4,0	29,0	0,27
	63,5		4,0	30,0	0,30
50	70,0	2 ½	4,0	31,5	0,35
	76,1	2 ½	4,0	33,0	0,39
	82,5		4,0	35,0	0,44
80	88,9	3	4,0	44,5	0,50
	95,0		4,0	46,0	0,55
	101,6	3 ½	4,0	47,5	0,62
100	108,0	4	4,0	49,0	0,68
	114,3	4	4,0	51,0	0,75
	121,0		4,0	52,5	0,82
125	127,0		4,0	54,0	0,90
	133,0	5	4,0	55,5	0,97
	139,7	5	4,0	57,5	1,06
150	152,4		4,0	60,5	1,12
	159,0	6	5,0	62,5	1,50
	168,3	6	5,0	65,0	1,80
200	219,1	8	6,0	78,5	3,50
250	273,0	10	6,0	92,0	5,20
300	323,9	12	8,0	111,0	8,50
350	355,6	14	8,0	119,0	10,00
400	406,4	16	8,0	132,0	15,20
500	508,0	20	10,0	163,5	26,30
600	610,0	24	12,0	200,0	46,00

Caps DIN 28011 - EN 10 028-2 - P265GH					
DN	D		T	H	kg/pc
	mm	inch			
20	26,9	¾	3,0	18,0	0,04
25	33,7	1	3,0	19,5	0,07
32	42,4	1 ¼	3,0	21,0	0,08
40	48,3	1 ½	3,0	22,0	0,11
	57,0	2	3,0	24,0	0,15
50	60,3	2	3,0	24,5	0,17
	70,0	2 ½	3,0	26,5	0,21
65	76,1	2 ½	3,0	27,5	0,25
80	88,9	3	3,0	39,0	0,32
	108,0	4	4,0	43,5	0,61
100	114,3	4	4,0	44,5	0,66
	133,0	5	4,0	48,0	0,84
125	139,7	5	4,0	49,5	0,96
	159,0	6	5,0	53,5	1,40
150	168,3	6	5,0	55,5	1,70
200	219,1	8	6,0	71,0	3,30
250	273,0	10	6,0	81,5	4,50
300	323,9	12	8,0	97,0	
350	355,6	14	8,0	103,5	9,80
400	406,4	16	8,0	113,0	12,40
500	508,0	20	10,0	139,0	
600	610,0	24	10,0	158,5	

Iné rozmery a akosti na požiadanie
Other dimensions and grades on request

Iné rozmery a akosti na požiadanie
Other dimensions and grades on request